

Trụ sở chính:

Đường số 2A, KCN Mỹ Xuân A,
Huyện Tân Thành, Tỉnh Bà Rịa -
Vũng Tàu, Việt Nam
Tel: 84 064 393 2333
Fax: 84 064 393 2338

Chi nhánh Cần Thơ

225 Đường 3/2, Phường Hưng
Lợi, Quận Ninh Kiều, TP.
Cần Thơ
Tel: 84 0710 383 9999
Fax: 84 0710 383 1111

Chi nhánh Hải Phòng

750 Nguyễn Văn Linh, Quận Lê
Chân, TP. Hải Phòng
Tel: 84 031 378 4555
Fax: 84 031 378 4666

Chi nhánh Hồ Chí Minh

270A Lý Thường Kiệt, Quận 10,
TP. Hồ Chí Minh
Tel: 84 08 3864 9800
Fax: 84 08 3864 9808

Chi nhánh Đà Nẵng

Lô 48, Đường số 4, KCN Đà Nẵng _
An Đồn, Quận Sơn Trà, TP. Đà Nẵng
Tel: 84 0511 393 1222
Fax: 84 0511 393 1228

Chi nhánh Hà Nội

Khu vực kho Nhà Máy Đông Tàu
Hà Nội, Phường Thanh Trì,
Quận Hoàng Mai, TP. Hà Nội
Tel: 84 04 3644 6555
Fax: 84 04 3644 6553

Chi nhánh Nha Trang

Số 131B, Đường 23/10, Phường Phương Sơn,
TP. Nha Trang, Tỉnh Khánh Hòa
Tel: 84 058 3821 085
Fax: 84 058 3821 086



Công Ty TNHH Công Nghiệp Gốm Bạch Mã (Việt Nam)

Đường số 2A, KCN Mỹ Xuân A, Huyện Tân Thành, Tỉnh Bà Rịa Vũng Tàu

WHITE HORSE CERAMIC INDUSTRIES (VIETNAM) CO.,LTD

Tel: 84 064 393 2333 Fax: 84 064 393 2338

Email: whvn@vnn.vn Website: www.whitehorseceramic.com.vn

The accuracy of colours shown in this brochure is as close as the printing process will allow. The appearance of tiles featured in this brochure may differ from the actual items sold. The pictures are only illustrative of the tile combinations. White Horse Ceramic Industries (VN) co., ltd reserves the right to amend the colour range or specifications of tiles at any time and without notice. All tile are packed in accordance with the standard packing list. For special orders and custom sizes, the products will be custom packed based on quantity and specification requested.

Độ chính xác của màu sắc trong catalogue chỉ mang tính chất tương đối của quy trình in cho phép. Màu sắc của gạch trong catalogue có thể khác so với thực tế. Hình ảnh chỉ mang tính chất minh họa. Công Ty TNHH Công Nghiệp Gốm Bạch Mã (Việt Nam) có quyền thay đổi màu sắc hoặc quy cách của gạch bất cứ lúc nào mà không cần báo trước. Tất cả các gạch được đóng gói theo tiêu chuẩn packing list. Đối với các đơn đặt hàng đặc biệt và kích thước theo yêu cầu, sản phẩm gạch sẽ được đóng gói riêng dựa theo số lượng và yêu cầu cụ thể.



LUMINARY SERIES



LUMINARY

OPEN MIND OPEN SPACE OPEN MIND OPEN SPACE

OPEN MIND OPEN SPACE OPEN MIND OPEN SPACE

OPEN MIND OPEN SPACE

OPEN SPACE
OPEN MIND OPEN SPACE



OPEN MIND OPEN SPACE

OPEN MIND OPEN SPACE

MIND OPEN SPACE

OPEN

MIND OPEN SPACE

OPEN SPACE

OPEN MIND OPEN SPACE




LUMINARY SERIES
M6002 · 600mm x 600mm / 24" x 24"




LUMINARY SERIES
M6003 600mm x 600mm / 24"x24"

OPEN SPACE **LUMINARY** OPEN MIND OPEN
OPEN MIND OPEN SPACE OPEN MIND OPEN SPACE
OPEN MIND OPEN SPACE OPEN MIND OPEN SPACE
OPEN MIND OPEN SPACE OPEN MIND OPEN SPACE
MIND OPEN SPACE OPEN MIND OPEN SPACE


OPEN MIND OPEN SPACE
LUMINARY OPEN SPACE




M6001 600mm x 600mm / 24"x24"



M6002 600mm x 600mm / 24"x24"



M6003 600mm x 600mm / 24"x24"



M6004 600mm x 600mm / 24"x24"

METAL SERIES

L63005

30mm x 600mm

L63006

30mm x 600mm

L63007

30mm x 600mm

L63008

30mm x 600mm

L63009

30mm x 600mm

WHITE HORSE TEST REPORTS

DIMENSIONS AND SURFACE QUALITY	HOMO TILES - GROUP B ₁		HOMO TILES - GROUP B ₁		HOMO TILES - GROUP B ₁	
	ISO 10545 Standard	White Horse Tiles (Test Result By SIRIM)	ISO 10545 Standard	White Horse Tiles (Test Result By SIRIM)	ISO 10545 Standard	White Horse Tiles (Test Result By SIRIM)
Length and Width	± 0.6%	Passed	Water Absorption	Maximum 0.5% Average 0.07% Individual Maximum 0.10%	Chemical Resistance To Household Chemical Of Glazed Tiles	Minimum GB No Visible Effect (GA)
Thickness	± 0.5%	Passed	Breaking Strength	Not Less Than 1000N Average 2000N	Chemical Resistance To Swimming Pool Salts Of Glazed Tiles	Minimum GB No Visible Effect (GA)
Straightness of Sides	± 0.5%	Passed	Modulus of Rupture	Minimum 35N/mm ² Average 65N/mm ² Individual Minimum 55N/mm ²	Chemical Resistance To Hydrochloric Acid (3%) Of Glazed Tiles	GLA No Visible Effect GLA
Rectangularity	± 0.6%	Passed	Resistance to Deep Abrasion of Unglazed Tiles	Maximum 125mm ² 120mm ²	Chemical Resistance To Citric Acid (100g/l) Of Glazed Tiles	GLB: Definite Change in Appearance GLA
Flatness of Surface	± 0.5%	Passed	Resistance to Surface Abrasion of Glazed Tiles	Class3: For Normal Footwear Class4: For Regular Traffic With Some Scratching Dirt	Chemical Resistance To Potassium Hydroxide (50g/l) Of Glazed Tiles	GLC: Partial Or Complete Loss Of The Original Surface GLA
Centre Curvature	± 0.5%	Passed				
Edge Curvature	± 0.5%	Passed				
Warpage	± 0.5%	Passed	Cracking Resistance	No Cracking Observed	Staining Resistance Test Of Glazed Tiles	Class5 (Stain Can Be Easily Removed With Pump-Hot Water)

SIZE	CARTON		PALLET	
	Pcs/Ctn	Pallet	M2/Ctn	M2/Pallet
60 cm x 60 cm	4	40	1.44	57.6
3 cm x 60 cm	60	60	1.08	64.80